



# 300 Rolling Window Brickmold Trim Package

## Creates a traditional exterior finish

Kas-Kel's 300 series new construction rolling windows feature an integrated brickmold trim package, which creates a traditional exterior finish.

The brickmold trim also serves as a J-channel pocket making for a clean finish look and easy installation.

### NFRC Thermal Performance Data\*

GLAZING	U-VALUE	SHGC	VLT	CR	ZONE
Energy Star U4	0.25	0.27	0.47	47	N,NC
Energy Star III	0.29	0.37	0.52	59	NC
Low E w/ Argon	0.29	0.29	0.52	59	NC
High Perf. Low E	0.33	0.29	0.52	56	
Clear	0	0	0	-	

\*contact us to see thermal data with grids.

**KAS-KEL NEW CONSTRUCTION WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.**



## Features

	STANDARD	OPTION	
<b>MATERIALS</b>	High-grade PVC delivers exceptional strength and thermal performance. White or beige Interior	✓	
	Fusion Welded Sash and Frame	✓	
	Removable Sash for cleaning	✓	
	Fully Weather Stripped Interlock	✓	
	Frame Depth 3 5/8"	✓	
<b>PERF</b>	DP 35 Rating	✓	
	DP 40 Rating		✓
<b>GLAZING</b>	Energy Star III	✓	
	Energy Star U-4		✓
	Clear insulated glass (3/4")		✓
	Duralite flexible, warm-edge spacers	✓	
	Tints, Heat Reflection and other options available		✓
<b>SCREENS</b>	Aluminum Extruded Fiberglass 1/2 screen	✓	
	Aluminum framed fiberglass full screen		✓
	Full Flexscreens on painted exteriors		✓
	Aluminum Screening Material		✓
<b>CONSTRUCTION</b>	Composite Reinforced Meeting Rail	✓	
	Integral Nail Fin	✓	
	Integral Nail Fin and J-Channel	✓	
	4 9/16", 6 9/16", and custom Pre-Primed Extension Jamb		✓
<b>GRILLS</b>	3/4" Contoured Grill Between the Glass		✓
	3/4" Contoured SDL with spacer bar		✓
<b>HARDWARE</b>	Ecoshield Rolling Windows are built on precision-calibrated rollers for long life and smooth fingertip operation.	✓	
	Cam Locks made to stand up to frequent use.	✓	
	All windows over 28 inches tall have 2 sash locks for maximum protection	✓	
	Produced in white or beige to seamlessly match your window frame	✓	

