



700 Series | Awning window

Easy operation and maximum ventilation

The accent window with all the bells and whistles.

The unique style and lines will catch your eye as will the performance and sizing features it includes. Stacked side by side or over the top of a primary window will work with great ease, giving you the flexibility needed when designing your home. Designed for today's generation.

GLAZING	U-VALUE	SHGC	VLT
DOE – R5 – Triple	0.19	0.19	0.33
Energy Star U-4	0.23	0.23	0.41
Energy Star III	0.26	0.32	0.44
Low E Argon	0.26	0.24	0.44
Low E HP	0.29	0.24	0.44
Clear	0.41	0.53	0.54

*contact us to see thermal data with grids.

Features

	STANDARD	OPTION
MATERIALS	High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior	<input checked="" type="checkbox"/>
	Fusion Welded Sash and Frame	<input checked="" type="checkbox"/>
	Beveled Exterior Sash	<input checked="" type="checkbox"/>
	Sash Snubbers	<input checked="" type="checkbox"/>
GLAZING	Energy Star III (recommended)	<input checked="" type="checkbox"/>
	Energy Star U-4	<input checked="" type="checkbox"/>
	DOE R5 Triple Glass Package	<input checked="" type="checkbox"/>
	Clear insulated glass	<input checked="" type="checkbox"/>
	Duralite flexible, warm-edge spacers	<input checked="" type="checkbox"/>
	Impact Resistance, Tints, Heat Reflection, and other options available	<input checked="" type="checkbox"/>
PERF.	DP 50 Rating	<input checked="" type="checkbox"/>
HARDWARE	Produced in white or beige to seamlessly match your window frame	<input checked="" type="checkbox"/>
	Single Lever Multi-Point Locking System	<input checked="" type="checkbox"/>
	Folding Hardware	<input checked="" type="checkbox"/>
CONSTRUCTION	Double weather stripped Sash	<input checked="" type="checkbox"/>
	1/2" and 3/4" Sheetrock Returns	<input checked="" type="checkbox"/>
	Nailing fin with J Channel	<input checked="" type="checkbox"/>
	Brickmold J Channel/ or no J Channel	<input checked="" type="checkbox"/>
SCREENS	Primed Solid Pine Applied Extension Jambes 4-9/16", 6-9/16" and Custom	<input checked="" type="checkbox"/>
	Extruded aluminum framed fiberglass full screen	<input checked="" type="checkbox"/>
GRILLS	Aluminum Screening Material	<input checked="" type="checkbox"/>
	3/4" Contoured Grill Between the Glass	<input checked="" type="checkbox"/>
	3/4" Contoured SDL with spacer bar	<input checked="" type="checkbox"/>
	2" Contoured SDL with spacer bar for simulated Double Hung look	<input checked="" type="checkbox"/>

KAS-KEL NEW CONSTRUCTION WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.

