

By design this window combines the beauty and performance you would expect to find in premium windows. Multiple point locking system with a clean fold away handle speaks volumes about our Casements. Configured with single or multi-unit combination for maximum ventilation. Fabricated for today's generation.

NFRC Thermal Performance Data*

GLAZING	U-FACTOR	SHGC	VLT	CR	ZONE
Energy Star U4	0.25	0.27	0.48	47	NC
Energy Star III	0.29	0.37	0.51	59	NC
Low E w/ Argon	0.28	0.28	0.51	63	NC
High Perf. Low E	0.32	0.28	0.51	58	N, NC
Clear	0	0	0	-	NC

^{*}contact us to see thermal data with grids.

KAS-KEL REPLACEMENT WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.









	Features	STANDARD	OPTION
	High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior	Ø	
ALS	Equal lite top and bottom sash	Ø	
MATERIALS	Full Fusion Welded Sash and Frame	Ø	
Ž	Sloped Sill and Interlock Leg	Ø	
	3-1/4" Frame Depth	Ø	
	DP 40 Rating		
PERF.	DP 50 Rating		
	Full 3" Foam insulating Wrap		
	Energy Star III		
BNI	Energy Star U-4		Ø
3'4" GLAZING	Clear insulated glass (3/4")		
3'4"	Duralite flexible, warm-edge spacers		
	Tints, Heat Reflection and other options available		Ø
S	Aluminum Extruded Fiberglass 1/2 screen		
	Aluminum framed fiberglass full screen		Ø
SCREENS	Extruded Aluminum framed locking 1/2 Screen		Ø
SC	Aluminum Screening Material		
	Full Flex Screens		②
	Our Cam Locks are made of alloyed cast steel to stand up to frequent use. (inferior vinyl windows have plastic locks)	Ø	
HARDWARE	All windows over 23 1/2 inches have 2 sash locks for maximum	Ø	
	Produced in white or beige to seamlessly match your window	Ø	
Ŧ	Night Latches	Ø	
	WOCD sash limiters		Ø
z	Composite Reinforced Meeting Rail		
UCTIC	Bottom and Top Sash Tilt in for easy cleaning	Ø	
CONSTRUCTIO	Double weather stripped Meeting Rail	Ø	
00	Full 3" Foam insulating Wrap		Ø
LS	5/8" Contoured Grill Between the Glass		
GRILLS	3/4" Contoured SDL with spacer bar		Ø

